

1 **CLAIMS**

2  
3 I Claim:

4  
5 1. An adjustable firearm support system, comprising:  
6 a base;  
7 a plurality of support members adjustably attached to said base; and  
8 a support unit pivotally attached to said base about a pivot axis, wherein said  
9 support unit is capable of supporting a firearm.

10  
11  
12 2. The adjustable firearm support system of Claim 1, wherein said base  
13 includes at least two front legs extending from a front portion of said base, wherein  
14 said front legs each include at least one of said support members.

15  
16  
17 3. The adjustable firearm support system of Claim 2, wherein said front legs  
18 extend outwardly from said base at an angle.

19  
20  
21 4. The adjustable firearm support system of Claim 2, wherein said base  
22 includes at least one of said support members extending from a rear portion of said  
23 base.

24  
25  
26 5. The adjustable firearm support system of Claim 1, wherein said support  
27 members allow for vertical adjustment of said base.

1           6. The adjustable firearm support system of Claim 5, wherein said support  
2 members are threadably connected to said base in a vertical manner.

3  
4  
5           7. The adjustable firearm support system of Claim 6, wherein said support  
6 members each include a locking collar for locking a desired vertical position with  
7 respect to said base.

8  
9  
10          8. The adjustable firearm support system of Claim 6, wherein said support  
11 members each include a pad member for engaging a surface.

12  
13  
14          9. The adjustable firearm support system of Claim 6, wherein said support  
15 members each include a handle for allowing rotation of said legs.

16  
17  
18          10. The adjustable firearm support system of Claim 1, wherein said base  
19 includes a handle opening.

20  
21  
22          11. The adjustable firearm support system of Claim 1, wherein said support  
23 unit includes a pivot axle that is rotatably retained within said base about said pivot  
24 axis.

25  
26  
27          12. The adjustable firearm support system of Claim 11, wherein said pivot axle  
28 is positioned within a front portion of said support unit.

1

2        13. The adjustable firearm support system of Claim 1, including a pivot  
3 adjuster attached to said base and connected to a rear portion of said support unit for  
4 pivoting said support unit about said pivot axis.

5

6

7        14. The adjustable firearm support system of Claim 13, wherein said pivot  
8 adjuster includes a pivot pin extending upwardly that is received by a support slot  
9 within said support unit.

10

11

12        15. The adjustable firearm support system of Claim 14, wherein said pivot  
13 adjuster is comprised of a threaded shaft with a threaded collar threadably positioned  
14 upon said threaded shaft and wherein said pivot pin is attached to said threaded collar.

15

16

17        16. The adjustable firearm support system of Claim 1, wherein said support  
18 unit includes a pair of side members and a support portion movably positioned  
19 between said side members, wherein said support member is adjustable in a vertical  
20 manner.

21

22

23        17. The adjustable firearm support system of Claim 16, wherein said support  
24 portion has a cutout for receiving a firearm.

25

26

27        18. The adjustable firearm support system of Claim 16, wherein said side  
28 members each include a side slot that each receive a support adjuster that is attached to  
29 opposing sides of said support portion.

1  
2  
3 19. The adjustable firearm support system of Claim 1, wherein said base has a  
4 Y-shaped structure.

5  
6  
7 20. An adjustable firearm support system, comprising:  
8 a base including a front portion, a rear portion and a handle opening, wherein  
9 said base has a Y-shaped structure;

10 a plurality of support members adjustably attached to said front portion and said  
11 rear portion of said base, wherein said support members are threadably connected to  
12 said base in a vertical manner for allowing vertical adjustment of said base, wherein  
13 each of said support members includes a locking collar for selectively locking a  
14 desired vertical position with respect to said base, wherein said support members each  
15 include a pad member for engaging a surface and wherein said support members each  
16 include a handle for allowing rotation of said legs;

17 at least two front legs extending from a front portion of said base, wherein said  
18 front legs each include at least one of said support members and wherein said front  
19 legs extend outwardly from said base at an angle;

20 a support unit pivotally attached to said base about a pivot axis, wherein said  
21 support unit is capable of supporting a firearm, wherein said support unit includes a  
22 pivot axle that is rotatably retained within said base about said pivot axis, wherein  
23 support unit includes a pair of side members and a support portion movably positioned  
24 between said side members, wherein said support member is adjustable in a vertical  
25 manner and wherein said support portion has a cutout for receiving a firearm and  
26 wherein said side members each include a side slot that each receive a support adjuster  
27 that is attached to opposing sides of said support portion;

28 a pivot adjuster attached to said base and connected to a rear portion of said  
29 support unit for pivoting said support unit about said pivot axis, wherein said pivot

1 adjuster includes a pivot pin extending upwardly that is received by a support slot  
2 within said support unit, and wherein said pivot adjuster is comprised of a threaded  
3 shaft with a threaded collar threadably positioned upon said threaded shaft and wherein  
4 said pivot pin is attached to said threaded collar.

5

6

7